

Installing The Roof Sheeting

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Debris in eyes	Eye Protection	
Cuts	Hand Protection	
Strains/Sprains	Steel Toed Boots	
Slips/Trips	Hard Hat	
	Hearing Protection	

Safe Work Procedure:

1. Snap a string line up on top of the rafter 48¼ inches from the outside of the fascia board.
2. Lift the sheeting material onto the roof rafters using good lifting techniques.
3. Position the sheet onto the first non-gable end rafter and center it on the rafter. Tack nail it in a couple of places.
4. Place subsequent sheets beside the previous set sheet and cut as necessary and tack them into place.
5. The next row of sheeting will be installed by staggering the sheets and cut to size to fill the remaining part of the roof.
6. Repeat this process for the other side of the roof.
7. Use a pneumatic nailer to complete all of the intermediate nailing.
8. Clean up the work area.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p>Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations:</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>