

Masonry Saw – Mounting a Blade

<b>Facility:</b>	<b>Written By:</b>	<b>Approved By:</b>	<b>Date Created:</b>	<b>Date of Last Revision</b>

<b>Hazards Present:</b>	<b>PPE or Devices Required:</b>	<b>Additional Training Required:</b>
Pinch Point	Steel toe boots	Read operators manual
Cuts	Safety glasses	
Electrical		

**Safe Work Procedure:**

- 1) Lock out saw to ensure no power supply.
- 2) Ensure work area is clean.
- 3) Use blade shaft wrench to loosen the collar to remove the blade shaft bolt.
- 4) Place the blade on the arbor.
- 5) Attach the loose collar and tighten the blade shaft bolt securely.

***If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure***

**REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR**

<p><b>Guidance Documents/Standards:</b></p> <p>MB Workplace Safety &amp; Health Act &amp; Regulations:  <b><i>Part 6 – Personal Protective Equipment</i></b>  <b><i>Part 16 – Machines and Tools</i></b></p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>