

Vibratory Asphalt Rollers

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
	Steel Toed Boots	
	Hard Hat	
	High Vis Vest	
	Long shirt/pants	

Safe Work Procedure:

- 1) Do a pre-trip inspection before starting the machine. Check for oil leaks or any damage to the equipment. Advise supervisor if machine requires immediate attention.
- 2) Mount/dismount the roller using three point contact
- 3) Check water pump operation for sprayers
- 4) Operators are required to start their equipment prior to the start of the shift
- 5) Move roller slowly forward and apply brakes to ensure they are working properly
- 6) Operate the machine at full throttle only.
- 7) When shutting down, apply the parking brake and allow the motor time to cool down
- 8) After parking the equipment, walk around the machine and visually inspection for leaks or damage.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards: MB Workplace Safety & Health Act & Regulations:	This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years
	Reviewed By WSH Committee: Date: