

Walk Behind Concrete Saw – Blade installation

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Pinch point	Safety glasses	See operators manual
Cuts	Steel toe boots	

Safe Work Procedure:

1. Raise the blade guard to its highest position.
2. Open blade nut access door, remove the blade shaft nut turning clockwise and remove the outside collar and raise the blade guard.
3. Position the blade beneath the cutting head and slide the blade into blade guard.
4. Locate blade shaft then slide the blade bore hole onto the blade shaft.
5. Slide the outside blade shaft collar onto the blade shaft, tighten the blade shaft nut counter-clockwise securely against the outside collar.
6. Close the blade nut access door.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p>Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations: <i>Part 6 – Personal Protective Equipment</i> <i>Part 16 – Machines and Tools</i></p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>