

## Dozer Operator

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Other workers and equipment	Steel toed boots	Operator training
Equipment malfunction	Hard hat	
Slip and trip		
Pinch points		

### Safe Work Procedure:

- 1) Use cold start procedure and do pre-trip inspection while machine is warming up
- 2) Check that:
  - there are no leaks or loose bolts
  - lights and back up alarm are working
  - hydraulics are running properly
- 3) Mount and dismount machine using 3 point contact
- 4) Proceed to work area checking steering and brakes as you go
- 5) Maintain proper distance from other workers and equipment and always look directly behind before backing
- 6) Pay constant attention to all gauges
- 7) When stopped, check machine over and do not drag winch cable or have hook dangling loosely
- 8) Park in safe area and drop the hydraulics
- 9) Use hot shut down procedure
- 10) Check over machine and clean rad and tracks when finished

***If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure***

**REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR**

<p style="text-align: center;"><b>Guidance Documents/Standards:</b></p> <p>MB Workplace Safety &amp; Health Act &amp; Regulations:</p> <p>6 Personal Protective Equipment 16 Machine, Tools and Robots 22 Powered Mobile Equipment</p>	<p style="text-align: center;">This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p> <p>Reviewed By WSH Committee:</p> <p>Date:</p>
--	--