

Gravel Patching

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Vehicle traffic	Coveralls, Gloves	
Pedestrian traffic	Hard hat	
Slips, trips, falls	Safety Glasses	
Moving equipment	Steel toed boots	
	Hi Vis Vest	

Safe Work Procedure:

- 1) Assess the location.
- 2) Place barricades
- 3) Fill depressions. Shovel or dump gravel/stone into depressions and soft spots. For small patches spread by hand, for large patches spread with a grader.
- 4) Compact patch material with a portable vibrating packer or alternatively with truck tires.
- 5) Remove warning signs/barricades

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p style="text-align: center;">Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations:</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>